

COVER-RITE™ Over Laminates



Product: Cover-Rite V6 T

Technical Data

Face Material	5.0 mil vinyl
Finish/Color	Slip Resistant/Clear
Adhesive	FG, Permanent Acrylic
Liner	1.2 mil polyester



UL-410 classified for slip resistance

Performance Characteristics

- High Volume and extended floor graphics applications.
- Scuff and Slip resistant finish

Typical Characteristics

Minimum Application Temperature	50°F	
Service Temperature Range	-40°F to +180°F	
Shelf Life (73°F, 50% RH)	2 years	
Target Adhesion Values (PSTC-1, 180 peel @ 12"/min. 73 F, on Stainless Steel	<u>15 min</u>	<u>24 hours</u>
Outdoor Life	140 oz	165 oz
Flammability	30 days	
	Self-Extinguishing	

Chemical Resistance

Distilled Water (24 hour)	No Effect
Detergent (24 hour)	No Effect
10% HCl (10 min)	N/A
10% Ammonium Hydroxide (10 min)	No Effect
Gasoline (1 hour)	No Effect

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

To place an order or get help call 1-800-276-2664
or visit our website at www.aglinc.com

Common Applications

- Floor Graphics
- Counter Graphics