

COVER-RITE™ Over Laminates



Product: **Cover-Rite P2.4 HCAG (ANTI-GRAFFITI)**

Technical Data

Face Material:	Clear Hard Coated Polyester
Finish/Color:	Gloss/Clear
Adhesive:	.9 mil Clear Acrylic
Liner:	105 gsm white silicone coating paper

Performance Characteristics

Adhesion Strength: 180° Peel Adhesion (kg/inch) (method: PSTC-1) > 1kg/inch

Shear Strength: 0° Shear Strength (hr/inch) (method: PSTC-7) > 54hrs/inch

Durability: Up to 2 years, vertical exposure outdoors

Application Temperature range: 40°F to 176°F

Cover-Rite P2.4 HCAG is a high quality laminating film suited to enhance and protect digital prints/images against the influence of UV, dirt and humidity. This film has excellent dimensional stability and enhanced image brightness. Cover-Rite P2.4 HCAG increases outdoor durability of the print and reduces fading and damage caused from outdoor exposure. This hard coat polyester film is an excellent over-laminate that provides resistance to many types of undesirable stains, inks, abrasions and solvents. Polyester laminating film are suited for medium to long term indoor or outdoor signage on flat or slightly curved surfaces with vertical exposure and application temperatures of 40° F to 176° F.

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

To place an order or get help call 1-800-276-2664
or visit our website at www.aglinc.com

Common Applications

- Transit Graphics
- Outdoor Signage in Public Places
- Bus Shelters, Train Depots, Sport Venues