

# COVER-RITE™ Over Laminates



## Product: Cover-Rite PP1G DE

### Technical Data

Face Material	1.0 mil Polypropylene non-treated
Finish/Color	Gloss/Clear
Adhesive	Overlaminating Permanent Acrylic
Liner	50 # White Glassine

### Performance Characteristics

- Non treated film for Write-On, Wipe-Off capability
- Used as coupon base for multilayered promotional labels

### Typical Characteristics

Minimum Application Temperature	50°F	
Service Temperature Range	-40°F to +180°F	
Shelf Life (73°F, 50% RH)	2 years	
Target Adhesion Values	<u>15 min</u>	<u>24 hours</u>
(PSTC-1, 180 peel @ 12"/min. 73 F, on Stainless Steel	1.4 lbs/in	2.0 lbs/in
Outdoor Life	1 year	

### Chemical Resistance

Distilled Water (24 hour)	No Effect
Detergent (24 hour)	No Effect
10% HCl (10 min)	No Effect
10% Ammonium Hydroxide (10 min)	No Effect
Anti-Freeze (24 hour)	No Effect
SAE 20 Motor Oil (24 hour)	No Effect

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

To place an order or get help call 1-800-276-2664  
or visit our website at [www.aglinc.com](http://www.aglinc.com)

## Common Applications

- Graphics Lamination
- Promotional Labels
- Coupons