

# COVER-RITE™ Over Laminates



**Product: Cover-Rite V2 G**

## Technical Data

Face Material	2.0 mil Premium cast vinyl
Finish/Color	Gloss/Clear
Premask	Clear-Removed by customer
Adhesive	Overlaminating Permanent Acrylic
Liner	1.2 mil polyester

## Performance Characteristics

- Overlamine wets out quickly to provide a clean image.
- Cast vinyl offers the maximum flexibility
- Stabilized vinyl film offers excellent protection from UV radiation to enhance the weathering of underlying graphics.

## Typical Characteristics

Minimum Application Temperature	50°F	
Service Temperature Range	-50°F to +225°F	
Shelf Life (73°F, 50% RH)	2 years	
Target Adhesion Values (PSTC-1, 180° peel @ 12"/min. 73 F, on Stainless Steel	<u>20 min</u>	<u>24 hours</u>
Outdoor Life	32oz	50 oz
60° Gloss	5 years	
	80 minimum	

## Chemical Resistance

Distilled Water (24 hour)	No Effect
Detergent (24 hour)	No Effect
10% Ammonium Hydroxide (10 min)	No Effect
Gasoline (10 min)	No Effect
SAE 30 Motor Oil (10 min)	No Effect

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

To place an order or get help call 1-800-276-2664  
or visit our website at [www.aglinc.com](http://www.aglinc.com)

## Common Applications

- Vehicle Graphics
- Window Graphics
- Graphics Lamination