

TM

# Cover-Rite

## Over Laminates



Digital Films Division

Product: Cover-Rite V3 SG

### Product Structure

Film	Semi-Gloss PVC
Adhesive	Solvent Acrylic (Heat Activated)
Release Liner	1 Side PE Coated Bleached Kraft Grey Grid Paper (Moisture Stable)

### Performance Characteristics

- Can be flush trimmed without danger of delamination.
- Excellent for textured images, Lambda output, laminating collage, or images that are die-cut.
- Bonds to inkjet output with high ink overage, even inkjet prints printed on photo gloss paper.

### Physical Characteristics

Film contains UV stabilizers, which prevent film degradation and provide UV protection to the underlying image.

Film Thickness	(2 mil)
Adhesive Layer	(1 mil)
Heat Resistance Range	158°F to 203°F
Peel Strength (20 min, FTM1)	18 N / 25mm
Outdoor Life	3 Years

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

To place an order or get help call 1-800-276-2664  
or visit our website at [www.aglinc.com](http://www.aglinc.com)

## Common Applications

- Trade Show Graphics
- Counter Graphics
- P-O-P Displays