

COVER-RITE™ Over Laminates



Product: Cover-Rite V475T

Technical Data

Face Material	3.75 mil Polyolefin
Finish/Color	Textured/Clear
Adhesive	Overlaminating Permanent Acrylic
Liner	1.2 mil clear film



UL-410 classified for slip resistance



This polyolefin overlaminate uses no plasticizers, lead, or phthalates in its construction. It is an environmentally friendly solution to replace polyester overlaminates.

Typical Characteristics

Minimum Application Temperature	50°F	
Service Temperature Range	-40°F to +180°F	
Shelf Life (73°F, 50% RH)	2 years	
Target Adhesion Values (PSTC-1, 180 peel @ 12"/min. 73 F, on Stainless Steel	<u>15 min</u>	<u>24 hours</u>
Outdoor Durability	65 oz	75 oz
	Indoor Use only	

Chemical Resistance

Distilled Water (24 hour)	No Effect
Detergent (24 hour)	No Effect
10% HCl (10 min)	No Effect
10% Ammonium Hydroxide (10 min)	No Effect
Gasoline (1 hour)	No Effect

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

To place an order or get help call 1-800-276-2664
or visit our website at www.aglinc.com

Common Applications

- Floor Graphics
- P-O-P Displays
- Counter Graphics