

COVER-RITE™ Over Laminates



Product: Cover-Rite V6e™ (TM354150)

Technical Data

Face Material	3.2 mil flexible vinyl
Finish/Color	Textured Matte/Clear
Adhesive	Overlaminating Permanent Acrylic
Liner	White Siliconized Paper

Performance Characteristics

- Protects and enhances images and graphics
- This product is available in widths up to 61+
- This product is listed as to slip resistance only SA45584
- UV Inhibitors protect from light absorption
- pH Neutral Adhesive - approx. 7.0

Typical Characteristics

Minimum Application Temperature	40°F
Application Temperature Range	40°F to +104°F
Shelf Life (73°F, 50% RH)	1 year
PSTC-1, 180 peel (kg/inch)	1 kg/inch
PSTC-7, 0 Shear Strength (hr/inch)	54 hrs./inch
Outdoor Life	2 years

Chemical Resistance

Distilled Water (24 hour)	No Effect
Detergent (24 hour)	No Effect
10% HCl (10 min)	N/A
10% Ammonium Hydroxide (10 min)	No Effect
Anti-Freeze (24 hour)	No Effect
SAE 20 Motor Oil (24 hour)	No Effect

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

To place an order or get help call 1-800-276-2664
or visit our website at www.aglinc.com

Common Applications

- Graphics Lamination