

Mount-Smart™ Mounting Adhesives



Product: Mount-Smart Bronze

Technical Data

Carrier Material	1.0 mil Polyester film
Adhesive	1.2 mil Permanent acrylic (unwind side)
Adhesive	1.1 mil Permanent acrylic (liner side)
Liner	74 lb polycoated kraft

Performance Characteristics

- General purpose acrylic adhesive designed for high quality graphic arts applications.
- Bonds well to substrates like "Gator" and "Sintra"
- Good resistance to heat, humidity, UV light, mild plasticizers and some solvents.

Typical Characteristics

Minimum Application Temperature	50°F	
Service Temperature Range	-35°F to +250°F	
Target Adhesion Values (PSTC #101)	<u>15 min</u>	<u>24 hours</u>
Liner Side	38-65 oz	55-85 oz
Unwind Side	45-75 oz	65-90 oz
Static Shear (PSTC #107, 1x1, 1000 gms, 72 F		24 hours +

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

To place an order or get help call 1-800-276-2664
or visit our website at www.aglinc.com

Common Applications

- Rigid Posters
- P-O-P Displays
- Promotional Products
- Decals