

Mount-Smart™ Mounting Adhesives



Product: Mount-Smart Clear Removable

Technical Data

Face Material	2.0 mil Polypropylene
Finish/Color	Clear
Adhesive	Permanent Acrylic one side (PA) Removable Acrylic one side, (LP)
Liner	1.2 mil polyester each side

Typical Characteristics

Minimum Application Temperature	50°F	
Service Temperature Range	-40°F to +180°F	
Shelf Life (73°F, 50% RH)	2 years	
Target Adhesion Values (PSTC-1, 180 peel @ 12"/min.)	<u>15 min</u>	<u>24 hours</u>
73 F, on Stainless Steel	(PA) 23 oz	31 oz
73 F, on Stainless Steel	(LP) 8 oz	9 oz
Shear (.5" x .5" x 500 gms)	24 hrs +	

NOTE: Due to varying dimensional stability of paper, this product is not recommended for use with paper stock.

Chemical Resistance

Distilled Water (24 hour)	No Effect
Detergent (24 hour)	No Effect
10% HCl (10 min)	No Effect
10% Ammonium Hydroxide (10 min)	No Effect
Anti-Freeze (24 hour)	No Effect
SAE 20 Motor Oil (24 hour)	No Effect
Gasoline (1 hour)	No Effect

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

To place an order or get help call 1-800-276-2664
or visit our website at www.aglinc.com

Common Applications

- Backlit Panels
- P-O-P Displays
- Promotional Products
- Temporary Graphics