

Mount-Smart™ Mounting Adhesives



Product: Mount-Smart Removable

Technical Data

Carrier Material	.5 mil Polyester film
Adhesive	1.2 mil Permanent acrylic (unwind side)
Adhesive	1.2 mil Removable acrylic (liner side)
Liner	74 lb polycoated kraft

Performance Characteristics

- Used when graphics are for temporary mounting and need to be removed.
- Permanent adhesive bonds well to high surface energy substrates
- Ultra removable adhesive is designed for clean removal from substrates.

Typical Characteristics

Minimum Application Temperature	50°F	
Service Temperature Range	-35°F to +150°F	
Target Adhesion Values (PSTC #101)	<u>15 min</u>	<u>24 hours</u>
Liner Side	3-7 oz / in	7-12 oz / in
Unwind Side	35-55 oz / in	45-60 oz / in
Static Shear (PSTC #107, 1x1, 1000 gms, 72°F)		
Liner Side	10 + hours	
Unwind Side	24 + hours	

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

To place an order or get help call 1-800-276-2664
or visit our website at www.aglinc.com

Common Applications

- Backlit Panels
- P-O-P Displays
- Promotional Products
- Temporary Graphics