

Print-Smart™ Vinyl Print Media



Product: **Print Smart HPV5 MW Permanent**

Technical Data

Face Material:	4 mil Calendered Polymeric PVC
Finish/Color:	Matte/White
Adhesive:	.9 mil Permanent Acrylic
Release Liner:	120 gsm White Siliconized double Kraft - Air Egress

Typical Characteristics

Average Adhesion Values	<u>20 min</u> >1200 g/inch	<u>24 hours</u> >1500 g/inch
Application Temperature:	50°F to 122°F	
Outdoor Durability	2 - 3 years, vertical exposure	
Heat Resistance:	41°F to 176°F	

Print-Smart HPV 5 is an easy to install solution for your short to medium-term permanent applications. This permanent adhesive allows for easy installation and long-term bond. Print-Smart HPV 5 is a high performance air egress vinyl for everyday sign applications. Designed for Solvent, Eco-Solvent, Latex based & UV inkjet printing on wide-format printing systems. Print-Smart HPV5 is a short to medium term outdoor signage on flat or slightly curved surfaces. Printed PVC must be allowed to dry for 24-48 hours at 70°F prior to lamination to allow residual solvent to evaporate. Failure to do so may result in unsatisfactory results.

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

To place an order or get help call 1-800-276-2664
or visit our website at www.aglinc.com

Common Applications

- Trade Show Displays
- Window Graphics
- Flat Panel Vehicle Graphics
- Medium Term Graphics