

Print-Smart™ Vinyl Print Media



Product: **Print-Smart V4 GCRR Removable Repositionable**

Technical Data

Face Material:	4.0 mil Calendered PVC
Finish/Color:	Gloss Clear
Adhesive:	Repositionable Removable Clear
Release Liner:	130 gram Anti Curl - Anti Wave

Typical Characteristics

Average Adhesion Values	<u>20 min</u> 9 oz/sq inch	<u>24 hours</u> 23 oz/sq inch
Opacity:	Clear	
Outdoor Durability:	1 year, vertical exposure	
Heat Resistance:	160°F Latex Recommended	

Print-Smart V4 GCRR is an easy to install solution for your short-term repositionable applications. The smooth, removable dot pattern of the adhesive allows for easy application and repositioning on smooth, nonporous surfaces. Designed for Solvent, Eco-Solvent, Latex based & UV inkjet printing systems. Double sided PE liner resists curling and waving due to humidity and high heat dryers. Printed PVC must be allowed to dry for 24-48 hours at 70 F prior to lamination to allow residual solvent to evaporate. Failure to do so may result in unsatisfactory results.

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

To place an order or get help call 1-800-276-2664
or visit our website at www.aglinc.com

Common Applications

- Smooth Surface Applications
- Promotional Decals
- Temporary Window Protection/Covering Film