

Print-Smart™ Vinyl Print Media



Product: **Print Smart V4 MWBOP Permanent**

Technical Data

Face Material:	4 mil Calendered PVC
Finish/Color:	Matte/White
Adhesive:	Permanent Blockout
Release Liner:	140 gram Air Egress Anti Curl - Anti Wave

Typical Characteristics

Average Adhesion Values	<u>20 min</u> 25oz/sq inch	<u>24 hours</u> 54oz/sq inch
Opacity:	99%	
Outdoor Durability	4 years, vertical exposure	
Heat Resistance:	104° F to 176° F Latex Recommended	

Print-Smart V4 MWBOP is an easy to install solution for your short to medium-term permanent applications. This permanent air egress adhesive allows for easy installation and long-term bond. Print-Smart V4 MWBOP is a premium air egress vinyl for everyday sign applications. Designed for Solvent, Eco-Solvent, Latex based & UV inkjet printing systems. Double sided PE liner resists curling and waving due to humidity and high heat dryers. Printed PVC must be allowed to dry for 24-48 hours at 70°F prior to lamination to allow residual solvent to evaporate. Failure to do so may result in unsatisfactory results.

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

To place an order or get help call 1-800-276-2664
or visit our website at www.aglinc.com

Common Applications

- Trade Show Displays
- Signage
- Medium Term Graphics